



हिमाचल प्रदेश केन्द्रीय विश्वविद्यालय Central University of Himachal Pradesh

धर्मशाला, जिला - कांगड़ा, हिमाचल प्रदेश - 176215
Dharamshala, District Kangra (HP)-176215

Ref. No: 06/2025-26/CUHP/ENGG/NIQ

Dated: 26.11.2025

NOTICE INVITING QUOTATION

For and on behalf of Central University of Himachal Pradesh, sealed Quotations are hereby invited by the undersigned for the work of **“Repair & maintenance works and Laying of sewerage pipeline damaged due to soil erosion caused by heavy rainfall at Shahpur Parisar”** from contractors/firms enlisted/ empaneled with Central/ State Govt. Organization/ Central Autonomous body/ Central Public Sector Undertaking as per schedule attached at **Annexure-II**. The sealed envelope containing quotation shall be super scribed with the **Name of Work, Quotation Enquiry Ref. No. and Date** and shall reach the O/o “Executive Engineer(C), CUHP (Construction site), Khabli Dosarka, Dehra, Distt. Kangra, H.P. - 177101” by registered post or delivered personally latest by **04.12.2025 upto 02:00 PM** and shall be opened on the same day at **02:30 PM** in the **“O/o Executive Engineer (C), CUHP (Construction site), Khabli Dosarka, Dehra, Distt. Kangra, H.P. - 177101”** in the presence of intending bidders/contractors or their authorized representatives.

Application for Quotation Document must be accompanied with the self-attested copies of the following qualifying documents:

- 1.) GST certificate.
- 2.) PAN Card.
- 3.) Certificate of enlistment with Central/State Govt. Organization/Central Autonomous body/Central Public Sector Undertaking.
- 4.) Signed copy of terms & conditions (Annexure-I)
- 5.) Schedule of quantities (Annexure-II)

The approximate cost of the work is Rs. 2,34,180 /- (Rupees Two Lakh Thirty-Four Thousand One Hundred Eighty only).

Detailed quotation document can be downloaded from the University website (www.cuhimachal.ac.in).

-sd-

Executive Engineer

Central University of Himachal Pradesh
Dehra, Distt. Kangra, Himachal Pradesh

Copy to:

1. Notice board.
2. University Website.

-sd-

Executive Engineer

Terms & Conditions:

1. The work is to be completed within **25 days**, to be reckoned from the 3rd day from date of award of work.
2. The quantities of work in the schedule (refer **Annexure- 'II'**) are provisional and likely to vary (increase or decrease).
3. The prices quoted should be net inclusive of CP&OH charges, freight, Labour, T&P, Cartage, Lead/Lift and GST and nothing extra is to be paid.
4. Security Deposit @ 2.5% of the final work done amount shall be deducted from the bills. This amount shall be released to the contractor after a period of six months from the completion of work.
5. Bidders are advised to visit the site before quoting the rates to assess the quantum and scope of work.
6. Payment shall be made only after the work is completed as per actual quantity and quantum of work executed satisfactorily; no advance shall be paid.
7. All material to be used on the work will have to be got approved from the Engineer-in-charge.
8. Compensation of delay of work will be @ 0.5% per day.
9. The quotation for the work shall have validity for a period of 60 days from the date of opening of quotations.
10. The contractor/firm has to abide by labour rules and regulations.
11. All applicable Taxes and Statutory Deductions shall be deducted from the final bill.
12. In case of any dispute, the decision of Vice-Chancellor, CUHP is final and binding on the contractor.
13. The Central University of Himachal Pradesh reserves the right to accept or reject any or whole quotation without assigning any reason thereof.
14. The firm/contractor shall be responsible for faithful compliance of the terms and conditions enunciated in this document. In the event of any breach of any of the terms and conditions, the assigned work may be terminated and further the work order may be got executed from another agency at risk and cost of the firm/Contractor.
15. In case of any queries/doubts the bidder(s) can visit/contact in the Office of Executive Engineer, CUHP (Construction site), Khabli Dosarka, Dehra, Distt. Kangra, H.P. – 177101 (Mob. 9459240775).

-sd-

Executive Engineer

Central University of Himachal Pradesh
Dehra, Distt. Kangra, H.P.

I acknowledge that I have read, and do hereby accept the terms and conditions contained in this quotation document.

Signature with date of bidder

Name (CAPITAL): _____

Address:

Contact no:

BILL OF QUANTITIES

Name of Work: Repair & maintenance works and Laying of sewerage pipeline damaged due to soil erosion caused by heavy rainfall at Shahpur Parisar					
Name of Bidder:					
S. No.	Description	Unit	Quantity	Rate (Rs.)	Amount (Rs.)
1	Earth work in surface excavation not exceeding 30 cm in depth but exceeding 1.5 m in width as well as 10 sqm on plan including getting out and disposal of excavated earth upto 50 m and lift upto 1.5 m, as directed by Engineer-in- Charge: All kinds of soil	sqm	12.25		
2	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level- 1:1½:3 (1 Cement: 1½ coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)	cum	1.428		
3	Distempering with 1st quality acrylic distemper (Ready mix) having VOC content less than 50 grams/ litre of approved brand and manufacture to give an even shade : Old work (one or more coats)	sqm	24.58		
4	Renewing glass panes, with putty and nails wherever necessary including racking out the old putty: Float glass panes of nominal thickness 4 mm (weight not less than 10kg/sqm) of size upto 0.1 sqm of each glass.	each	98.00		
5	Taking out existing wooden door shutter, repair by cutting, painting etc. and refixing of repaired door shutters to existing door frames, including replacement of hinges with screws, etc. as required, all complete as per the direction of the Engineer-in-charge.	no	2.00		
6	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	sqm	4.57		
7	Providing and fixing precoated galvanised steel sheet roofing accessories 0.50 mm (+0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete : Ridges plain (500 - 600mm)	m	3.00		
8	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS:733 and IS:1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately). For fixed portion: Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	kg	18.32		

9	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS:733 and IS:1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately). For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	kg	22.43		
10	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 4.0 mm thickness (weight not less than 10kg/sqm)	sqm	4.49		
11	Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 35 kg and door width upto 700 mm), with necessary accessories and screws etc. complete.	no	1.00		
12	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : 150x10 mm	no	4.00		
13	Providing and fixing aluminium handles 125 mm, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete.	no	6.00		
14	Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete: 250x16 mm.	no	1.00		
15	Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete: Twin rubber stopper.	no	2.00		
16	Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows, fixing with butt hinges of required size with necessary screws, excluding panelling which will be paid for separately, all complete as per direction of Engineer-in-charge. (Note:- Butt hinges and necessary screws shall be paid separately): Kiln seasoned and chemically treated hollock wood 35 mm thick shutters.	sqm	2.64		
17	Providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25 mm to 40 mm thick : Ply wood 5 ply, 9 mm thick Decorative plywood one side decorative veneer and commercial veneer on other face (Type 1) conforming to IS 1328 BWR Type	sqm	0.66		
18	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes 110 mm diameter	m	78.00		

19	Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion: Bend 87.5°, 110 mm bend	no	22.00		
20	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture	sqm	4.44		
21	Taking out C.I. cover with frame from R.C.C. top slab of inspection chambers of various sizes including demolishing of R.C.C. work manually/by mechanical means and stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead as per direction of Engineer-in-charge.	no	1.00		
22	Supplying and fixing C.I. cover without frame for manholes : 455x610 mm rectangular C.I. cover (light duty) the weight of the cover to be not less than 23 kg	no	1.00		
23	Supplying, filling, spreading & leveling stone boulders of size range 5 cm to 20 cm, in recharge pit, in the required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.	cum	1.225		
24	Providing and fixing 4 mm thick ACP sheet exterior grade in panelling fixed in aluminum doors, windows shutters and partition frames with EPDM rubber / neoprene gasket etc. complete as per architectural drawings and directions of engineer-in-charge.	sqm	4.88		
25	Providing and fixing PVC wall panelling having panel thickness 5mm (+/- 0.25mm) and 10 inch width including interlocked edges, centre groove of 6mm width and 1mm depth for sinking the head of screw used to fix the strips on wall vertically, complete. The colour, finish, design of PVC panels should be aesthetically pleasing with interiors of the location and should have impact resistance, durability, resistance to environmental factors (high and low temperature, moisture etc.)	sqm	42.62		
26	Providing and fixing 0.63 mm thick Galvanised steel pain sheet in wall cladding, MS grills, wooden doors fixed with necessary screws, PVC sleeves, welding etc. complete as per directions of engineer-in-charge.	sqm	1.58		
27	Excavating trenches of required width for pipes, cables, etc including excavation for sockets, and dressing of sides, ramming of bottoms, depth upto 1.5 m, including getting out the excavated soil, and then returning the soil as required, in layers not exceeding 20 cm in depth, including consolidating each deposited layer by ramming, watering, etc. and disposing of surplus excavated soil as directed, within a lead of 50 m : All kinds of soil: Pipes, cables etc. exceeding 80 mm dia. but not exceeding 300 mm dia	m	20.00		
28	Providing and laying cement concrete 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) all-round S.W./ UPVC pipes including bed concrete as per standard design : 150 mm diameter pipe	m	20.00		
29	Constructing brick masonry manhole in cement mortar 1:4 (1 cement : 4 coarse sand) with R.C.C. top slab with 1:1.5:3 mix (1 cement : 1.5 coarse sand (zone III) : 3 graded stone aggregate 20 mm nominal size), foundation concrete 1:4:8 mix (1 cement : 4 coarse sand (zone-III) : 8 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement complete as per standard design : Inside size 90x80 cm and 45 cm deep including C.I. cover with frame (light duty) 455x610 mm internal dimensions, total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg) : With common burnt clay F.P.S. (non modular) bricks of class designation 7.5	no	1.00		

30	Making connection of drain or sewer line with existing manhole including breaking into and making good the walls, floors with cement concrete 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) cement plastered on both sides with cement mortar 1:3 (1 cement : 3 coarse sand), finished with a floating coat of neat cement and making necessary channels for the drain etc. complete: For pipes 100 to 250 mm diameter	each	2.00		
31	Providing and laying UPVC pipes in underground drainage work with necessary fittings, solvent etc. complete : (i) Single socketed pipes : 150 mm diameter	m	20.00		
		Total (in Rs.)			
	Total Amount in Words:				

-sd-

Executive Engineer

Central University of Himachal Pradesh

Dehra, Distt. Kangra, H.P.

Signature of bidder

Name: _____

Address: _____